

- 13

Vf

position, means for counting one of said pulses from a particular position, and means for rejecting those of said pulses which originate from said particular position and in a time interval on the order of the neutron die-away time in polyethylene or other suitable material.

- 5
8. The apparatus of claim 1, wherein said neutron detectors are grouped in pods.
9. The apparatus of claim 8, further including a plurality of means for counting and a like plurality of veto means, and wherein ^{all} said detectors included in ^{a particular one} ~~each~~ of said pods are coupled to a one of said plurality of means for counting and to one of said veto means, said veto means vetoing said counting of said additional one of said pulses from all of said detectors included in said pod.
10. The apparatus of claim 9, further including means for vetoing said counting of said additional ones of said pulses from all of said detectors included in each of said pods which are adjacent to said pod which includes said detector which produced said pulse which was counted.
11. The apparatus of claim 8, wherein there are at least 10 of said pods.
12. The apparatus of claim 1, wherein said detectors are supported by a layer of material which shields said waste from neutrons generated outside of said layer.
13. The apparatus of claim 1, further including means for disabling said veto means for high counting rates.
- Sub A2 > 14. A method for increasing the sensitivity of measuring the amount of radioactivity in waste by reducing the interference caused by cosmic ray generated neutrons, said method including the steps of:

Sub A2

5

- a) providing a plurality of neutron detectors, each of said detectors including means for generating a pulse in response to the detection of a neutron;
- b) counting only some of said pulses from each of said detectors, whether cosmic ray or fission generated; and
- c) vetoing the counting of additional ones of said pulses from each of said detectors for a prescribed period of time after said counting.

10

15. The method of claim 14 wherein said prescribed period of time is between 50 and 200 μ s.

Add A3